

**1. Identification of the Substance/Preparation and Company**

Product name: **Elkem Microsilica** ®

Product application: Cementitious systems

Address/Phone No.: **Elkem ASA,  
Materials**  
P.O.Box 8126 Vaagsbygd  
N-4675 Kristiansand, Norway  
Telephone: + 47 38 01 75 00  
Telefax: + 47 38 01 49 70  
<http://www.materials.elkem.com>

Contact person: Arne Skagen, e-mail: [arne.skagen@elkem.no](mailto:arne.skagen@elkem.no)

Emergency Phone No.: Not applicable

**2. Composition/Information on Ingredients**

Synonyms: Silica fumes, Microsilica, Silica powder, Amorphous silica, Silicon dioxide powder, condensed SiO<sub>2</sub>-fume, Silica fume.

IUPAC-name: Silicon dioxide

CAS No.: 69012-64-2  
EINECS No.: 273-761-1

Symbols and indications of danger: None  
R and S Phrases: None

Microsilica may contain small amounts of crystalline quartz (<0.5%).

**3. Hazards Identification**

The product is unlikely to cause harmful effects when handled and stored as advised.

#### 4. First Aid Measures

Inhalation: Remove exposed person from dusty area. Fresh air.  
Skin contact: Wash contaminated skin with water and/or a mild detergent.  
Eye contact: Rinse eyes with water/saline solution. If discomfort persists, obtain medical attention.  
Ingestion: Not applicable.

#### 5. Fire Fighting Measures

The product is not combustible and the dust entails no danger of explosion.

Extinguishing media: Not applicable

#### 6. Accidental Release Measures

Avoid exposure to dust of the product. Released material should be collected in suitable containers.

#### 7. Handling and Storage

Handling: Avoid dust generation. See section 8.  
Storage: Keep away from hydrofluoric acid (HF).  
Not to be stored at temperatures near to or below 0°C.

#### 8. Exposure Controls/Personal Protection

##### A) Occupational exposure controls:

Avoid inhalation of dust. Ensure good dust ventilation during use. Wear a CE-marked respirator according to EN 149 FFP 2S/3S during dust generating operations. Use protective gloves and eye protection. Facilities for Eye flushing should be available.

Occupational Exposure Limits (ACGIH <sup>1)</sup> , 2005):		8hr TWA		ACGIH TLV 15 minute STEL		Notations
Substance	[CAS No.]	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	
Silica fume (SiO <sub>2</sub> )	[69012-64-2]	-	2 <sup>(R)</sup>	-	-	-
Silica, crystalline (SiO <sub>2</sub> ) Quarz*	[14808-60-7]	-	0,05 <sup>(R)</sup>	-	-	A2
	Cristobalite [14464-46-1]	-	0,05 <sup>(R)</sup>	-	-	-

- <sup>1)</sup> American Conference of Governmental Industrial Hygienists  
\* Changes are proposed in the NIC (Notice of Intended Changes)  
<sup>(R)</sup> Respirable fraction

##### B) Environmental exposure controls:

See sections 6, 7 and 12.

Limit values ambient air (Directive 1999/30/EC):

	Averaging time	Limit value
PM <sub>10</sub> ★	24 Hrs	50 µg/m <sup>3</sup>
PM <sub>10</sub>	Calendar year	40 µg/m <sup>3</sup>

★ not to be exceeded more than 35 times a calendar year

## 9. Physical and Chemical Properties

Form:	Ultrafine amorphous powder (respirable dust), dust forms agglomerates.
Colour:	Grey
Odour:	Odourless
Melting Point (°C):	1550-1570
Solubility (Water):	Insoluble/Slightly soluble
Solubility (Organic solvents):	Insoluble/Slightly soluble
Specific Gravity (water =1):	2.2-2.3
Bulk density (kg/m <sup>3</sup> ) approx.:	150-700
Specific surface (m <sup>2</sup> /g):	15-30
Particle size, mean (µm):	≈ 0.15 (≈ 80 weight% of primary particles have a diameter < 5 µm).

## 10. Stability and reactivity

Conditions to avoid:	See below
Materials to avoid:	Hydrofluoric acid (HF).

### Hazardous Decomposition Product(s):

The product reacts with hydrofluoric acid (HF) forming toxic gas (SiF<sub>4</sub>).  
Heating the product above 1000°C can result in the formation of crystalline SiO<sub>2</sub>-modifications as cristobalite / tridymite which may cause pulmonary fibrosis (silicosis).

## 11. Toxicological Information

### Acute effects:

INGESTION:	Finely divided dust may cause mechanical irritation and dehydration of mucous membranes.
INHALATION:	Finely divided dust may cause mechanical irritation and dehydration of mucous membranes.
SKIN CONTACT:	Finely divided dust may cause mechanical irritation and dehydration.
EYE CONTACT:	Finely divided dust may cause mechanical irritation and dehydration.

### Chronic effects:

Inhalation of dust from the product is considered to entail minimal risk of pulmonary fibrosis (silicosis). However, chronic obstructive lung disease is suspected following long term exposure (years) for concentrations above recommended occupational exposure limits.

## 12. Ecological Information

The product is not characterised as dangerous for the environment.

MOBILITY:	The product is not mobile under normal environmental conditions.
PERSISTENCE:	Not relevant for inorganic substances.
BIOACCUMULATION:	Not relevant.
ECOTOXICITY:	Elkem Microsilica: <i>Daphnia magna</i> : 24 h EC <sub>50</sub> > 1002 mg.l <sup>-1</sup> 24 h EC <sub>100</sub> >1002 mg.l <sup>-1</sup> NOEC 319 mg.l <sup>-1</sup> Coarse microsilica has been subject to Microtox™ screening test. No acute toxicological effects could be observed in the test organisms.

### 13. Disposal Considerations

The material should be recovered for recycling if possible.  
This material is not classified as hazardous waste according to Commission Decisions 2000/532/EC and 2001/118/EC. Prior to disposal of large quantities of this material advice should be sought from the relevant Waste Regulation Authority.

### 14. Transport Information

UN	-
IMDG/IMO	Not subject to classification
ADR/RID	Not subject to classification
ICAO/IATA	Not subject to classification

### 15. Regulatory Information

Product classification and labelling:

Symbol:	Not subject to classification
R-phrases:	None
S-phrases:	None

The text of this Data Sheet is prepared in compliance with:

- Commission Directive 2001/58/EC.
- Council Directive 67/548/EEC and its subsequent amendments.

### 16. Other Information

Literature references are available upon application to the manufacturer.

Elkem Microsilica<sup>®</sup> is a registered trademark owned by Elkem ASA.